



## Vehicle Load Pan Tilt HZH320

### Features:

1. Aluminum alloy structure, IP66 waterproof.
2. All weather design, capture object quickly at night without light, night vision range more than 100M, up to 500M with laser illumination (optional)
3. Rotation range: Pan: 360°continuous , tilt :-90°~+90°,
4. Support HD SDI camera
5. Support OSD menu
6. 128 preset positions, cruising track with preset title display.
7. 6 programmed cruising tracks, 3 auto scans,16 privacy masks
8. Built-in anti-lightning and surge protection, support power failure memory
9. Support AC24V and 12V, used for vehicle load.



**Parameters:**

Model	HZH320
Pan Rotation Range	0°~360°continuous rotation
Tilt Rotation Range	-90°~+90°
Pan Speed Range	0°/s~100°/S
Tilt Speed Range	0°/s~60°/S
Preset	128
Auto Scan	3 ( set start and end position, scan speed is adjustable, automatic scan angle identification according to start and end position )
Cruise Track	6 (each with1 preset position, dwell time is adjustable)
Different Scan	3 (each more than 2minutes)
Privacy Masking	Yes, different brand camera with different privacy masking zones ( for camera with privacy masking function)
Menu	Chinese/English menu
Menu Password Protection	Support
Soft Address	Easy to change camera address
Automatic Homing Function	Homing time( 1~99minutes) and homing movement (preset/scan/cruise/different scan) can be set
Display Function	Display horizontal and vertical position, lens status, dome address, temperature, time
Temperature Sensor	Yes, users can set a different temperature for automatic blower or manually control
Control Protocols	Support 16 protocols, support AD/PHILIPS Manchester Code
Baud Rate	Baud rate 2400/4800/9600/19200bps optional
Camera	Support multi-brand network HD cameras, SDI cameras
Heater/Defroster/Wiper	Yes
IR Distance	< 80m
IR LED Enable	Auto/manual
Protection	IP66
Working Temperature	- 35℃ ~ 55℃
Power Supply	AC24V/ DC12V
Weight	5kg

※ ZHOAN will not inform the change of characteristic and specification

※ ZHOAN has the right to change design and specifications caused by improving product. Web information is just for reference, the details please follow real product and confirm with sales before purchase.